Installation Instructions – Flush Mount Track



Before Installing – Assess the installation setting suitability

Important: Prior to installation, we recommend confirming the wall structure itself can support the intended artwork weights. Our track systems are strong, but only as strong as the sub-structure they are attached to.

Absolute's Flush Mount Track, with 300mm top and bottom staggered hole centres, can support individual artworks weighing up to 150kg (up to 1x 150kg artwork per linear metre). To hang artworks of such weights, the track must be fixed to continuous hardwood or plywood platens within the wall structure to support the load. **For advice, please contact us prior to installation.**

- 1. Hold the first section of track in place and mark the positions of the track screw holes. Make sure that the edge marked "top" is uppermost. The position of the track is determined by the design requirements; it is frequently placed lower than the ceiling line.
- 2. Drill and fix the first section of track in place starting making sure you choose the relevant fixings for the type of ceiling you are attaching to (4mm diameter screws are best suited to this track. The length of screw is determined by the wall structure.)
- 3. Tap one of the connecting pins (supplied) into the small 2mm hole at the end of the track so that half of a pin protrudes and engages with the next section of track, ensuring everything aligns neatly.
- 4. Repeat this process until you reach the last section of track and trim the track to the appropriate length.
- 5. Absolute's Flush Mount Track is designed to be mostly hidden in the wall so that only the slim channel is exposed. Note that the face of the channel must be flush with the finished face of the upper and lower wall. Also, the Hanging Top Blocks toggle into place and require a 27-degree clearance directly above the channel.

Tip: For the smoothest overall finish, mitre inside and outside corners using a chop saw for a clean continuous finish.

To hang artworks, you will need to use Flush Mount Track Hanging Sets (See Hanging Set Instructions).